



ELF MOTO FORK OIL SYN

2,5W
5W
10W

Elf Moto Fork Oil Syn is the new range of very high performance synthetic fork oils. They have been specially formulated for motorcycle forks and shock absorbers and ensure the best possible performance in the most severe conditions of use.

APPLICATION

MOTORCYCLE FORKS AND SHOCK ABSORBERS

- Specially formulated to satisfy all the requirements of the different types of motorcycle telescopic forks and hydraulic shock absorbers.

SUITABLE GRADES

- There are different grades for all types of machine (on or off-road), all types of driving (solo or duo) and different modes of driving (touring or racing).
A low viscosity (SAE 2.5W or 5W) is more particularly recommended for rapid response at high damper amplitude (for example in cross-country use), and a high viscosity (SAE 10W) for perfect performance on the road and motorway.

SPECIFICATIONS

SYNTHETIC

- The base oils in the fluids for forks and shock absorbers are 100% synthetic

SAE 2.5 – 5 and 10W

- To obtain a grade of SAE 7.5W the 5W and 10W grades can be mixed 50/50.



CLIENT ADVANTAGES

ANTI-WEAR	<ul style="list-style-type: none"> The ELF MOTO FORK OIL SYN fork oils consist of synthetic bases fortified by special additives that confer a number of qualities, for example high anti-wear capability.
OPTIMUM ABSORPTION	<ul style="list-style-type: none"> The oil permits optimum absorption at all times of year, which remains stable with time.
QUIK DE-AERATION	<ul style="list-style-type: none"> Excellent performance with regard to air: limited foaming and rapid de-aeration.
HIGH VISCOSITY MAINTAINS PERFORMANCE	<ul style="list-style-type: none"> Thanks to its <i>naturally high viscosity number</i>, the performance level offered by ELF MOTO FORK OIL SYN remains unchanged over time.
OUTSTANDING LIFE	<ul style="list-style-type: none"> High resistance to oxidation, which guarantees outstanding life; the ELF MOTO FORK OIL SYN range also has excellent antirust and anticorrosion properties.
COMPATIBILITY	<ul style="list-style-type: none"> Excellent compatibility with the elastomers used in motorcycle forks and shock absorbers.

CHARACTERISTICS

	2.5W	5W	1 0W	
Colour	Red	Red	Red	
Specific gravity at 15 °C	0.826	0.829	0.838	
Viscosity number		121	130	135
Kinematic viscosity at 40 °C	18	23.3	45.4	mm ² /s
Kinematic viscosity at 100 °C	4	4.8	7.6	mm ² /s
Pour point	<-51	<-51	<-45	°C

(Typical values given for illustration)

This lubricant when used according to our recommendations and for the purpose for which it is intended presents no particular hazard

A safety data sheet complying with current EU legislation can be obtained from your local commercial advisor

21/05/01



ELF MOTO FORK OIL SYN